INDIGO
Be surprised!

Exterior Emulsion



PRODUCT DESCRIPTION

Indigo Exterior Emulsion is a water based emulsion that provides protection for shaded exteriors. It has been designed to provide better hiding & coverage and a smooth matt finish.

PERFORMANCE FEATURES & BENEFITS

Anti-algal

- Excellent resistance to chalking, cracking and weathering in comparison to cement paint.
- It gives neat and clean shades
- Non Fading shades

FINISH

MATT GLOSSY

WASHABILITY

NO LOW **MEDIUM** HIGH

RECOMMENDED USES

AREA

☐ INTERIOR ☑ EXTERIOR

SURFACES

Concrete, walls and Masonary Surface

APPLICATION DETAILS & SURFACE PREPARATION

MIXING
Shake well before use

TOOLS
Brush, Roller & Spray

THINNING
Water

THINNING RATIO
65-75%
65-75% by Volume

SURFACE DRYING TIME
30
Surface Dry in 30 Min.

FILLING
Indigo Polymer Putty or Acrylic Wall Putty

APPLICATION ENVIRONMENT
Temperature: 10-40 Degree
Humidity: Below 80%

CLEANING
Clean the surface of loose paint, dust and grease. Scrub vigorously with wire brush to remove algae, fungus and moss growth, especially on horizontal surfaces prone to water stagnation.

SURFACE PREPATION
Seal cracks with a 1:3 mixture of cement and sand. Use of Indigo Polymer Putty is highly recommended. Allow 3 months curing prior to painting for newly plastered surfaces. Freshly plastered surfaces require a self-priming coat, obtained by thinning 1L of paint with 1L of water.

APPLICATION
Apply 2 coats of Indigo Exterior Emulsion, obtained by thinning 1L of emulsion with 650-700 ml of water. 3 Coats are recommended for horizontal surfaces like ledges, sun-shades, etc.

SAFETY FEATURES
Non- flammable
No added Lead, Mercury or Chromium compounds

Exterior Emulsion

TECHNICAL DATA

Coverage	1 Coat: 10 - 12 sqm/L* 2 Coat: 6 - 7 sqm/L*
Drying Time	4-5Hrs
Sheen level	2.2 at 60 deg
Flash point	NA
Stability of thinned paint	24Hrs
Appearance	Smooth,Liquid, White
Solids	61
Specific gravity	1.3 to 1.49
Recommended DFT	NA
Viscosity @25°C by Stormer Viscometer	2100 cp
Pot life	24 hrs
Shelf life	24 months
Contrast ratio	98.5

**Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.*

PRECAUTIONS

1. Do not apply in rainy season, apply only on properly dry surface
2. Tinted paint needs to be shaken immediately after tinting

POST APPLICATION INSTRUCTIONS

For best performance, ensure proper washing and cleaning of all algal and fungal growth if any, at the regular interval of six months.

AVAILABLE PACK SIZE

Available in:



SHADE RANGE

As per Shade Card & Indigo Colour Fandeck

INDIGO
Be surprised!

For more information on our products and services contact 02931 281 162 or visit us at www.indigopaints.com
INDIGO Paints Pvt Ltd, 103 Montreal, Baner Road 411 045, India