INDIGO
Be surprised!

Premium XT Exterior Emulsion



PRODUCT DESCRIPTION

Indigo Premium XT Exterior Emulsion is specially designed to withstand extreme weather conditions with superior anti-fungal and anti-algae properties.

PERFORMANCE FEATURES & BENEFITS

- Weather Guard
- Dirt Pickup Resistance
- Anti-fungal & Anti-algal

FINISH

MATT GLOSSY

WASHABILITY

NO LOW MEDIUM **HIGH**

RECOMMENDED USES

AREA

☐ INTERIOR ☑ EXTERIOR

SURFACES

Concrete, Walls and Masonary Surface

APPLICATION DETAILS & SURFACE PREPARATION

MIXING
Shake well before use

TOOLS
Brush, Roller & Spray

THINNING
Water

THINNING RATIO
40-50%
40-50% by Volume

SURFACE DRYING TIME
30
Surface Dry in 30 Min.

FILLING
Indigo Polymer Putty or Acrylic Wall Putty

APPLICATION ENVIRONMENT
Temperature: 10-40 Degree
Humidity: Below 80%

CLEANING
Clean the surface of loose paint, dust and grease. Scrub vigorously with wire brush to remove algae, fungus and moss growth, especially on horizontal surfaces prone to water stagnation.

SURFACE PREPATION
Seal cracks with a 1:3 mixture of cement and sand. Use of Polymer Putty is highly recommended. Allow 3 months curing prior to painting for newly plastered surfaces. Apply 1 coat of Indigo Exterior Wall Primer, obtained by thinning 1 litre of primer with 1 litre of water.

APPLICATION
Apply 2 coats of Indigo Premium XT Exterior Emulsion, obtained by thinning 1 L of laminate with 400-500 ml of water. 3 Coats are recommended for horizontal surfaces like ledges, sun-shades, etc.

SAFETY FEATURES
Non- flammable
No added Lead, Mercury or Chromium compounds

Premium XT Exterior Emulsion

TECHNICAL DATA

Coverage	1 Coat: 10 - 12 sqm/L* 2nd Coat: 7 - 8 sqm/L*
Drying Time	4-5Hrs
Sheen level	2.2 at 60 deg
Flash point	NA
Stability of thinned paint	24Hrs
Appearance	Smooth, Liquid, White
Solids	61
Specific gravity	1.3 to 1.49
Recommended DFT	NA
Viscosity @25°C by Stormer Viscometer	1900 CP
Pot life	24 hrs
Shelf life	24 months
Contrast ratio	98.5

**Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.*

PRECAUTIONS

1. Do not apply in rainy season, apply only on properly dry surface
2. Tinted paint needs to be shaken immediately after tinting

POST APPLICATION INSTRUCTIONS

For best performance, ensure proper washing and cleaning of all algal and fungal growth if any, at the regular interval of six months.

AVAILABLE PACK SIZE

Available in:



SHADE RANGE

As per Shade Card & Indigo Colour Fandeck

INDIGO
Be surprised!

For more information on our products and services contact 02931 281 162 or visit us at www.indigopaints.com
INDIGO Paints Pvt Ltd, 103 Montreal, Baner Road 411 045, India