



BISON

ACRYLIC INTERIOR EMULSION



Product Attributes



Value for money

Better finish than distemper at almost the same cost

Coverage
Spreads twice as much as distemper thereby covers twice the wall space



XP Advanced Range

Bison XP Advanced gives better whiteness, lower smell and higher coverage compared to regular Bison emulsion

Anti-fungal

Resists growth of algae, fungus and moulds



Green Pro Certified

Validates our effort in striving towards cleaner, more sustainable future

Product Description

Bison emulsion has a smooth and stylish matt finish, making it an ideal choice for the price conscious customer. It has twice the durability of a distemper and is suitable for a wide variety of surfaces. It is formulated with special colour fast pigments with excellent anti-fading properties.

Recommended Use

Sand-cement plaster surface, asbestos, brickwork, concrete block and fiberboard

Colour Range



10,000 shades

Finish



Smooth and stylish matt finish

Toxicity



VOC - 50 gm/L
Dry film is non-toxic, with no added lead and arsenic

Coverage

120-140 sqft/Lt/2 coats

(Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

Recommended Undercoats

Primer: For wall/ plastered surfaces - BP Cement Primer WT (Alkali Resistant)

Putty: For wall/ plastered surfaces - Bison Wall Putty / Happy Wall Putty

Number of Coats:

2 coats of emulsion for re-painting provided the colour is same.

3 coats of emulsion if fresh painting is required to give a rich matt look.

Application Method



Brush / Roller / Spray

Recommended Thinner / Cleaner



Potable water

Dilution Ratio



For Brush application: 500 ml of water/ L of emulsion

In case of N base shades, no dilution is advised to ensure proper colour depth.

Drying Time



SD: 15 - 25 min depending on weather conditions **HD:** 6 - 8 hours



BISON

ACRYLIC INTERIOR EMULSION



Packs



1 Ltr 4 Ltr 10 Ltr 20 Ltr

White and PO

Packs of 1, 4, 10 and 20 Lt

ColorBank

Pack of 0.9, 3.6, 9 and 20 Lt

Bases

PO, W1, N2, Yellow and Cream, N



Fire Hazard Class
Non-flammable



Pot Life of Thinned Material
Overnight

Surface Preparation



For fresh/ new surfaces, ensure the surface is clean and dry and free from all loose particles, chalk, grease, fungus and algae. Sand the surface with Emery Paper No. 80 and wipe clean.



Apply the first coat of primer and allow it to dry for 6 – 8 hours.



Smoothen the surface by applying thin coats of putty to fill in all the dents. Allow the putty to dry overnight.



Sand the surface with Emery Paper No. 100 and wipe clean. Apply the second coat of primer and allow it to dry for 6 – 8 hours. Sand the surface with Emery Paper No. 220 and wipe clean.

For Previously Painted Surfaces: Strip all the old paint and remove all the loose particles before starting the above process of primer and putty application.

Directions for Application

Dilute the paint as per the recommended dilution ratio. Apply the first finishing coat and allow it to dry for at least 6 -8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

Cleaning Instructions

Use only toilet soap to clean stains

Use only a soft white cotton cloth for cleaning

While cleaning, wipe gently without using pressure

Attempt cleaning the surface only after one week of application

Points to Note

- ▶ Shake well before use and do not over dilute
- ▶ Strain the material through a fine sieve before use
- ▶ Keep the container tightly closed to prevent drying
- ▶ Use one coat of Bio – Wash for killing fungal growth
- ▶ Scrape off old paint thoroughly before painting starts
- ▶ Gyro shake well after tinting through CB Machine
- ▶ For deep shade apply one additional coat
- ▶ Do not apply paint on lime washed surfaces and damp wall
- ▶ In case of contact with eyes, wash immediately with water and seek medical help

Version No: BPP1/11/2014. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com