



Exterior Wall Primer

PRODUCT DESCRIPTION

Indigo Ext.Wall Primer is a water-based wall coating, suitable for application on exteriors as an under coat to exterior emulsion.

PERFORMANCE FEATURES & BENEFITS

Excellent opacity, whiteness and adhesion to top coat emulsion.
Does not chalk and does not require any water curing

FINISH

MATT

GLOSS

WASHABILITY

NO

LOW

MEDIUM

HIGH

OTHER PRODUCT RELATED FEATURES

Good opacity and whiteness

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

Exterior cement plasters, exterior ceilings, asbestos sheets, concrete etc. as an undercoat.

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Shake well before use

TOOLS



Brush

THINNING



Water

THINNING RATIO



85 - 90% by vol.

SURFACE PREPARATION



Standard surface preparation required

DRYING TIME



Surface Dry in 30 Min.

APPLICATION ENVIRONMENT



Between 5 to 40 Degree temp and below 80% humidity

CLEANING



Remove all dust, dirt, chalking, oil, grease, loose particles and all other contamination. Any previous growth of fungus and algae should be removed by wire mesh and cleaned with water. Let it dry completely and apply a coat of Indigo Bio-wash. Allow it to react minimum 5-6 hrs.

FILLING



Indigo Polymer Putty or Acrylic Wall Putty

SAFETY FEATURES



Non- flammable, no added Lead, Mercury or Chromium compounds. Refer MSDS.



Spray application: Air-assisted spray application at pressure 25 - 30 psi

* Recoat period is quoted for 25° C and 50% Relative Humidity; these may vary under different conditions.

TECHNICAL DATA

| | |
|---------------------------------------|-------------------------|
| Coverage | 1 Coat: 10 - 12 sqm/L** |
| Drying Time | 4-5 Hrs |
| Sheen level | 2.0 at 60 degree |
| Flash point | NA |
| Stability of thinned paint | 24 Hrs |
| Appearance | Smooth, Liquid, White |
| Solids | 52 % |
| Specific gravity | 1.4 |
| Recommended DFT | - |
| Viscosity @25°C by Stormer Viscometer | 2345cp |
| Practical Spreading Rate | - |
| Pot life | 24 hrs |
| Shelf life | 24 months |
| Contrast ratio | 95.8 |

*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

PRECAUTIONS

In coastal area do not leave primer without application of top coat, do not over thin, and shake well and strain before use

POST APPLICATION INSTRUCTIONS

Apply Indigo Emulsion paint on primer

AVAILABLE PACK SIZE

Available in:



SHADE RANGE

White



INDIGO
Be surprised!