



Interior Emulsion

PRODUCT DESCRIPTION

Indigo Interior Emulsion is a specially developed economical product with a smooth finish and better whiteness, opacity and coverage as compared to normal distemper. It is formulated by using ideal combination of pigments and extenders, dispersed in a copolymer emulsion for smooth and pleasant matt finish.



PERFORMANCE FEATURES & BENEFITS

Economical Emulsion

FINISH

MATT

GLOSS

WASHABILITY

NO

LOW

MEDIUM

HIGH

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

Concrete & Walls

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Shake well
before use

TOOLS



Brush & Roller

THINNING



Water

THINNING RATIO



50-55% by Volume

SURFACE DRYING TIME



Surface Dry in 30 Min.

FILLING



Indigo Polymer Putty
or Acrylic Wall Putty

APPLICATION ENVIRONMENT



Temperature:
10-40 Degree
Humidity: Below 70%

CLEANING



Clean the surface of loose paint,
dust and grease by sanding with
emery paper.
Wipe clean with a soft cloth.

SURFACE PREPARATION



Apply Indigo Cement Primer. After drying for 8
hours, fill the dents in the surface with Polymer
Putty. Repeat sanding with emery paper, wipe
clean, and apply another coat of Indigo Cement
Primer. After drying for 8 hours, sand with fine
emery paper & wipe clean.

APPLICATION



Apply 2-3 coats of Indigo Interior
Emulsion, obtained by thinning 1 L of
emulsion with 500-550 ml of water.

SAFETY FEATURES



Non- flammable
No added Lead, Mercury or
Chromium compounds

TECHNICAL DATA

Coverage	1 Coat: 14 - 15 sqm/L* 2nd Coat - 8 - 9 sqm/L*
Drying Time	4-5 Hrs
Sheen level	2.4 at 60 degree
Flash point	NA
Stability of thinned paint	24 Hrs
Appearance	Smooth, Liquid, White
Solids	50 %
Specific gravity	1.38
Recommended DFT	NA
Viscosity @25°C by Stormer Viscometer	1900 CP
Pot life	24 hrs
Shelf life	24 months
Contrast ratio	93.55

*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

PRECAUTIONS

1. Wall should be free from moisture
2. If any wall is under seepage, treat it with proper waterproofing
3. Do not apply on any lime washed surfaces
4. In case of fungi or algae use Indigo Bio Clean to clean the surface

POST APPLICATION INSTRUCTIONS

NA

AVAILABLE PACK SIZE

Available in:



SHADE RANGE

As per Indigo Colour Fandek



INDIGO
Be surprised!