



NEROLAC

BEAUTY SMOOTH FINISH INTERIOR EMULSION



PRODUCT DESCRIPTION

Nerolac Beauty Smooth Finish Interior Emulsion is a specially developed, economical interior emulsion for a distinctly rich and smooth finish. Its optimum performance, with respect to decoration and protection, is through an ideal combination of pigments and extenders, dispersed in a copolymer emulsion.

PERFORMANCE FEATURES & BENEFITS



RECOMMENDED USAGE

Nerolac Beauty Smooth Finish Interior Emulsion is recommended for interior wall surfaces such as ceilings, plasters, bricks, asbestos, etc.

RECOMMENDED SYSTEM FOR APPLICATION

For New Masonry Surfaces

1 Primer** (1 coat) Dry in 4 - 6 hrs.

2 Putty## Dry in 6 - 8 hrs.

3 Primer** (1 coat) Dry in 4 - 6 hrs.

4 Finish Nerolac Beauty Smooth Finish Interior Emulsion (2-3 coats)
Dry min. 4-6 hrs. in between coats.

Sand the surface with Emery paper and wipe clean before application of subsequent coat.

**Nerolac Cement Primer (water thinnable / solvent thinnable) or Goody Universal Primer (Solvent thinnable) or Goody water thinnable Cement Primer

##Nerolac Wall Putty or Nerolac Cement Putty

*Minimum 8 hrs for Solvent Thinnable Primer & minimum 4-6 hrs for Water Thinnable Primer

SURFACE PREPARATION

- 1 Ensure the surface is clean, dry, "free from all defective or poorly adhering material, dirt, grease, wax etc. Remove all loose or poorly adhering materials by rubbing down, using suitable abrasive paper and thereafter wipe off.
- 2 Treat fungus-affected area using Nerolac Fungicidal Solution. Allow it to react for 6 - 8 hrs.
- 3 Apply a coat of suitable Primer** followed by Nerolac Wall Putty# to level the dents and make the surface uniform.
- 4 Again apply a coat of suitable Primer**.
- 5 Then apply two to three coats of Nerolac Beauty Smooth Finish Interior Emulsion.

For Repainting on Smooth Lime / Distemper / Emulsion / Enamel Masonry Surfaces skip steps 1 and 2 and start with step 3

TECHNICAL DATA



COVERAGE***

17.65-20.43 sq.mt/ltr/coat when applied to smooth and non-absorbent surface



DRYING TIME

Surface Dry: 30 minutes



RECOATING

Min. 4 - 6 hrs. (@27°± 2°C & RH 60 ± 5%)



GLOSS LEVELS/SHEEN LEVELS

Matt



VOC IN GM/KG OR GM/L

< 50 gms/ltr



THINNING

40 - 50% by volume using water.



FLASH POINT

NA



STABILITY OF THINNED PAINT

Use within 24 hrs



DRY FILM THICKNESS (IN MICRONS) /COAT

15-20 :- Brush
25-30 :- Roller



WASHABLE

Moderate



***Actual coverage may vary depending on Method, Condition of Application, Type of Tools, Surface Porosity & Shade. Use of Felt Roller may reduce coverage upto 50%.

PRECAUTIONS



1. Refer MSDS for "Nerolac Beauty Smooth Finish Interior Emulsion" for safety measures & precautions.
2. Store in well-ambient conditions, ventilated locations & away from sources of ignition and fire.
3. Keep away from children.
4. In case of eye / skin contact, wash with plenty of water.
5. Inhalation / Injection can be dangerous. In either case, move to fresh air & consult medical practitioners.
6. Do not apply when ambient temperature might drop to levels below 10°C within 4 hrs of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. Can be tinted with Nerolac Hi-Power Universal Stainer before thinning. Do not add more than 5% of Nerolac Hi-Power Universal Stainer. Stir the tinted paint well, after tinting & before application.
10. The container must be tightly closed when not in use. Stir well and strain before use.
11. Use safety equipments like rubber or polythene gloves, safety goggles / glasses & face mask.

POST APPLICATION INSTRUCTIONS

Surfaces painted with Nerolac Beauty Smooth Finish Interior Emulsion are washable by sponging with mild soap and water after a minimum of 2 weeks drying to remove ordinary stains and everyday dirt.

SAFETY FEATURES:

Non-Flammable.

PACK SIZES:

1 Ltr, 4 Ltrs, 10 Ltrs, & 20 Ltrs.

SHADE RANGE:

As per Beauty Range Shade Card & Colour Scapes Fandec.

NO. OF SHADES POSSIBLE:

More Than 1400

