



NEROLAC

IMPRESSIONS 24 CARAT

PREMIUM LUXURY EMULSION



PRODUCT DESCRIPTION

Nerolac Impressions 24 Carat water based luxury emulsion gives your walls an exquisite look with clear HD colours & a rich smooth finish. It stays awe inspiring for years with excellent washability & superior stain resistance.

PERFORMANCE FEATURES & BENEFITS



RECOMMENDED USAGE

Nerolac Impression 24 Carat Premium Luxury Emulsion is designed for application on new as well as previously painted interior surfaces such as plaster, brickwork, cement rendering, concrete, hard boards etc.

RECOMMENDED SYSTEM FOR APPLICATION

For New Masonry Surfaces

1 Primer** (1 coat) Dry in 4 - 6 hrs.

2 Putty## Dry in 6 - 8 hrs.

3 Primer** (1 coat) Dry in 4 - 6 hrs.

4 Finish Nerolac Impressions 24 Carat Emulsion (2-3 coats)
Dry min. 3-4 hrs. in between coats.

Sand the surface with Emery paper and clean before application of subsequent coat.

**Nerolac Cement Primer (water thinnable / solvent thinnable) or Goody Universal Primer (Solvent thinnable/Goody water thinnable Cement Primer

##Nerolac Wall Putty or Nerolac Cement Putty

#Minimum 8 hrs for Solvent thinnable Primer & Minimum 4-6 hrs for Water thinnable Primer

SURFACE PREPARATION

- 1 Rub the surface using a suitable abrasive paper and wipe it off to ensure that the surface is clean, dry# and free from dirt, grease, wax or any other defective or poorly adhering material.
- 2 Treat fungus affected areas using Nerolac Fungicidal Solution and allow it to react for 6 - 8 hrs.
- 3 Apply a coat of Nerolac Cement Primer** (water/solvent thinnable) followed by Nerolac Wall Putty## /Nerolac Cement Putty# (wherever required) to level and smoothen the surface.
- 4 Sand the surface with Emery paper 220 & wipe clean.
- 5 Apply another coat of primer** on puttied areas.
- 6 Sand the surface with Emery paper 320 & clean the surface with cloth before painting.
- 7 Finally, apply two to three coats of Impressions 24 Carat emulsion as per recommended thinning. Dark shades may require additional coat for hiding.

For Repainting on Smooth Lime / Distemper / Emulsion / Enamel Masonry Surfaces skip steps 1 and 2 and start with step 3

TECHNICAL DATA



COVERAGE***

On smooth and non-absorbent surface
20.44-22.30 sq. mt/ltr/coat



DRYING TIME

Surface Dry: 30 minutes



RECOATING

3 – 4 hrs. (@27⁰± 2°C & RH 60 ± 5%)



GLOSS LEVELS/SHEEN LEVELS

Sheen



VOC IN GM/KG OR GM/L

< 50 gms/ltr

THINNING
40 - 50% by volume using water.



FLASH POINT
NA



STABILITY OF THINNED PAINT
Use within 24 hrs



DRY FILM THICKNESS (IN MICRONS) /COAT
20-25 : Brush
30-35 : Roller



WASHABLE
High



***Actual coverage may vary depending on Method, Condition of Application, Type of Tools, Surface Porosity & Shade. Use of Felt Roller may reduce coverage upto 50%.

PRECAUTIONS



1. Refer MSDS for "Nerolac Impressions 24 Carat Premium Luxury Emulsion" for safety measures & precautions.
2. Store in well-ambient conditions, ventilated locations & away from sources of ignition and fire.
3. Keep away from children.
4. In case of eye / skin contact, wash with plenty of water.
5. Inhalation / Injection will cause danger. In either case, move to fresh air & consult medical practitioners.
6. Do not apply when ambient temperature might drop to levels below 10°C within 4 hrs of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. Can be tinted with Nerolac Hi-Power Universal Stainer before thinning. Do not add more than 5% of Nerolac Hi-Power Universal Stainer. Stir the tinted paint well, after tinting & before application.
10. The container must be tightly closed when not in use. Stir well and strain before use.
11. Use safety equipments like rubber or polythene gloves, safety goggles / glasses & face mask.

POST APPLICATION INSTRUCTIONS

For removing stains, sponge clean with a mild soap solution and wipe clean. Please allow 1 week of drying time to freshly painted wall for it to be ready for stain removal / cleaning.

SAFETY FEATURES:

Non-Flammable.

PACK SIZES:

1 ltr, 4 ltrs, 10 ltrs, & 20 ltrs.

SHADE RANGE:

As per Nerolac Color Deck & Shade Card

NO. OF SHADES POSSIBLE:

More Than 1450

