



WEATHERCOAT GLOW

PREMIUM EXTERIOR SMOOTH EMULSION



Product Attributes



Stay Clean

Comes with unique dirt repellent properties to wash off dust with every rain

Weather Protection

Provides complete weather protection from rain and heat



Sheen Finish

With a rich sheen finish, it enhances the beauty of your house



Anti Algal and Anti Fungal

Protection against exterior wall issues



5 years performance warranty

Green Pro Certified

Validates our effort in striving towards cleaner, more sustainable future




Product Description

Weathercoat Glow is a 100% acrylic emulsion that provides unmatched protection and performance to your exterior walls. The paint has added silicon which imparts enhanced water repellence to the paint film. It has been designed to withstand diverse weather conditions and comes with a rich sheen finish.

Recommended Use

Exterior plastered surfaces and concrete blocks

Colour Range



Over 2,000 shades

Finish

- GLOSS
- HIGH SHEEN
- SHEEN ✓
- MATT

Rich Sheen

Toxicity



VOC - 36.9 gm/lt

Coverage

55- 60 sq.ft/ lt/2 coats, under ideal test conditions. (Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

Recommended Undercoats

Primer: For wall/plastered surfaces – WeatherCoat Exterior Primer

Putty: For wall/plastered surfaces – Bison Wall Putty

Recommended Surface

Sand, cement plaster, asbestos, brickwork, concrete block and fiberboards

Drying Time



SD: 25-35 min depending on weather conditions

HD: 3-4 hours

Dilution of dark shades only



Maximum dilution should be 10 – 15 % depending on shade. Coverage may be less compared to light shades.

Application Method



Brush / Roller / Spray

Recommended Thinner



Potable water

Dilution Ratio



Brush: 400 ml of water/1L emulsion

Gloss Level



4-8 at 60° GH when released



WEATHERCOAT GLOW

PREMIUM EXTERIOR SMOOTH EMULSION



Packs



ColorBank/ Non-ColorBank – Pack
0.9, 1, 3.6, 4, 9, 10 and 20 L

Bases

PO, W1, N, N1, N2, Cream, Yellow, Brown and White



Fire Hazard Class
Non-flammable



Pot Life of Thinned Material
Overnight

Surface Preparation




For fresh/new surfaces: Strip all loose particles from the surface with wire brushing and by scraping, followed by a wipe down. Wash the surface down with water and allow it to dry.



Apply 1 or 2 coats of Berger Bio-Wash solution (5%v/v) and allow it to dry overnight.



Wash it again the next day with potable water. Allow the surface to dry fully.



Apply one coat of primer and allow it to dry for 6–8 hours.

For Previously Painted Surfaces: Strip all the old paint and remove all the loose particles before starting the above process.

Directions for Application

Dilute the paint as per the recommended dilution ratio. Apply the first finishing coat and allow it to dry for at least 6-8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

Special Note

Before painting, the following things should be checked thoroughly:

- ▶ Ideal moisture content of the wall should be below 12%
- ▶ Ideal pH value of the wall surface should be between 7-11

Points to Note

- ▶ Shake well before use and do not over dilute
- ▶ Strain the material through a fine sieve before use
- ▶ Keep the container tightly closed to prevent drying
- ▶ Scrape off old paint thoroughly before painting starts
- ▶ Gyro shake well after tinting through CB Machine
- ▶ Do not apply paint on lime washed surfaces or damp wall
- ▶ Keep out of reach of children and away from foodstuff
- ▶ In case of contact with eyes, wash immediately with water and seek medical help

Version No: BPP1/12/2020. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com