



# Interior Sheen Emulsion

## PRODUCT DESCRIPTION

Indigo Interior Sheen Emulsion is a value for money product that gives a premium soft glow finish at a reasonable price.



## PERFORMANCE FEATURES & BENEFITS

- Provides best in class sheen finish for a premium look.
- Value for money, rich finish at a price close to Distemper.
- Based on modified acrylic binder, hence washable paint film.
- Durable finish.
- Excellent surface coverage.

### FINISH

MATT **SHEEN** GLOSS

### WASHABILITY

NO LOW **MEDIUM** HIGH

## RECOMMENDED USES

### AREA

☒ INTERIOR ☐ EXTERIOR

### SURFACES

Concrete, Brick and Masonary Surface

## APPLICATION DETAILS & SURFACE PREPARATION

### MIXING



Shake well before use

### TOOLS



Brush, Roller & Spray

### THINNING



Water

### THINNING RATIO



50-60% by Volume

### SURFACE DRYING TIME



Surface Dry in 30 Min.

### FILLING



Indigo Polymer Putty or Indigo Acrylic Wall Putty

### APPLICATION ENVIRONMENT



Temperature: 10-40 Degree  
Humidity: Below 70%

### CLEANING



Clean the surface of loose paint, dust and grease by sanding with emery paper. Wipe clean with a soft wet cloth.

### SURFACE PREPARATION



Apply Indigo Cement Primer. After drying for 8 hours, fill the dents in the surface with Acrylic Wall Putty. Sand using abrasive paper, wipe clean. Apply another coat of Indigo Cement Primer. After drying for 8 hours, sand with abrasive paper & wipe clean.

### APPLICATION



Apply 2-3 coats of Indigo Interior Sheen Emulsion, obtained by thinning 1 L of emulsion with 500-600 ml of water.

### SAFETY FEATURES



No added Lead, Mercury or Chromium compounds

## TECHNICAL DATA

<b>Coverage</b>	1st Coat: 22- 23 sqm/L * 2nd Coat: 12 - 14 sqm/L*
<b>Drying Time</b>	4-5 Hrs
<b>Sheen level</b>	60 at 85 deg
<b>Flash point</b>	NA
<b>Stability of thinned paint</b>	24Hrs
<b>Appearance</b>	Smooth, Liquid, White
<b>Solids</b>	51%
<b>Specific gravity</b>	1.32 - 1.38
<b>Recommended DFT</b>	NA
<b>Viscosity @30°C by Stormer Viscometer</b>	1800 CPs
<b>Pot life</b>	NA
<b>Shelf life</b>	36 Months
<b>Contrast ratio</b>	min 97

\*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

## PRECAUTIONS

1. Wall must be cured completely & free from moisture.
2. If any wall is under seepage, treat it with proper waterproofing before painting.
3. Do not apply on any lime washed surfaces.

## POST APPLICATION INSTRUCTIONS

For the best performance of the paint, ensure proper cleaning of all dust, oil and external particles, if any, at regular intervals of 6 months, using mild soap solution and soft sponge.

## AVAILABLE PACK SIZE

Available in:



## SHADE RANGE

As per Indigo Colour Fandek



**INDIGO**  
Be surprised!