



Acrylic Distemper

PRODUCT DESCRIPTION

Indigo Acrylic Distemper is a water based Interior paint which gives matt finish to walls.



PERFORMANCE FEATURES & BENEFITS



Durable

Matt Finish

FINISH

MATT

GLOSS

WASHABILITY

NO

LOW

MEDIUM

HIGH

RECOMMENDED USES

AREA



INTERIOR



EXTERIOR

SURFACES

Plaster Walls

APPLICATION DETAILS & SURFACE PREPARATION

MIXING



Shake well before use

TOOLS



Brush & Roller

THINNING



Water

THINNING RATIO



50-60% by Volume

SURFACE DRYING TIME



Surface Dry in 20 Min.

FILLING



Indigo Polymer Putty or Acrylic Wall Putty

APPLICATION ENVIRONMENT



Temperature: 10-40 Degree
Humidity: Below 70%

CLEANING



Remove all loose and flaking particles, and rub with sand paper. Ensure that the surface is clean and dry.

SURFACE PREPARATION



Newly plastered surfaces should be allowed to mature for a minimum period of 6 months before painting.

APPLICATION



Apply one coat of Indigo Cement Primer. After filling up dents with a layer of Indigo Polymer Putty, apply another coat of Cement primer. Apply 2-3 coats of Indigo Acrylic Distemper, obtained by thinning 1kg of distemper with 500-600 ml of water.

SAFETY FEATURES



Non- flammable
No added Lead, Mercury or Chromium compounds

TECHNICAL DATA

Coverage	1st Coat: 10-11 sqm/kg * 2nd Coat: 6-7 sqm/kg *
Drying Time	4-6 Hrs
Sheen level	2.3 at 60 degree
Flash point	NA
Stability of thinned paint	NA
Appearance	Semi Solid
Solids	67
Specific gravity	1.63
Recommended DFT	NA
Viscosity @25°C by Stormer Viscometer	430 psi by Penetrometer
Pot life	24 hrs
Shelf life	24 months
Contrast ratio	99.7

*Practical Spreading Rate will vary from the quoted Theoretical Spreading Rate due to factors such as method and condition of application as well as surface roughness.

PRECAUTIONS

Do not apply when the ambient temperature below 10°C. Do not apply directly on Lime wash or White cement painted wall

POST APPLICATION INSTRUCTIONS

NA

AVAILABLE PACK SIZE

Available in:



SHADE RANGE

As per Shade Card



INDIGO
Be surprised!